



Can

SUITABLE FOR CHRYSLER APPLICATION



ANTI FRICTION MOVEMENT
ROUND THE GLOBE



Can Bearing No.	O.E.M	Bore Dia(mm)	Outer Dia(mm)	Total Bearing Height(mm)	Illustration
45449/45410	72 GB 1200 AA	29.000	50.292	14.224	
47686/47620	2986842	82.550	133.350	33.340	
5840		43.600	69.800	18.600	
CA-103	658998 658998 658998 658998 635529	38.100	71.200	17.000	
CA-103 -S4	2072852 2072852	0.000	0.000	0.000	
CA-108	1664510 1664510 16645510 1664510	52.300	90.400	20.200	
CA-153	D 71257 D 71257	63.500	103.300	22.000	
IR-5041		14.200	34.800	10.300	
N833	53384	52.400	83.489	20.701	
RMS9	P43652 9188096	28.575	71.438	20.640	



V. Kan. Export

AN ISO/TS 16949:2009 CERTIFIED CO.

WORKS: PLOT NO.: 347, SECTOR-8, IMT-MANESAR, GURUGRAM-122050, HARYANA (INDIA)
TELEFAX: +91-124-406-7421, +91-9810049380, +91-9810099961
E.MAIL : canbearing@gmail.com , vaibhav.ahuja82@gmail.com

www.canbearings.com