



SUITABLE FOR DODGE APPLICATION



ANTI FRICTION MOVEMENT
ROUND THE GLOBE



Can Bearing No.	O.E.M	Bore Dia(mm)	Outer Dia(mm)	Total Bearing Height(mm)	Illustration
5813	640086/376751 640086/376751 640086/376751 640086/376751	33.300	49.200	11.500	
6202-Z		15.000	35.000	11.000	
CA-108	4821211330 5048669 5048669 1654510 1654510 1664510 1664510 1664510	52.300	90.400	20.200	
CA-132	73028517	65.000	101.500	22.000	
CA-153	D 71257 D 71257 D 71257 D 71257	63.500	103.300	22.000	
F1 10085	2072060/062	20.100	38.100	7.800	
IR-5016		22.200	38.000	9.200	
IR-5063		46.000	64.000	10.000	



V. Kan. Export

AN ISO/TS 16949:2009 CERTIFIED CO.

WORKS: PLOT NO.: 347, SECTOR-8, IMT-MANESAR, GURUGRAM-122050, HARYANA (INDIA)
TELEFAX: +91-124-406-7421, +91-9810049380, +91-9810099961
E.MAIL : canbearing@gmail.com , vaibhav.ahuja82@gmail.com

www.canbearings.com