



Can

SUITABLE FOR HYUNDAI APPLICATION



ANTI FRICTION MOVEMENT
ROUND THE GLOBE



Can Bearing No.	O.E.M	Bore Dia(mm)	Outer Dia(mm)	Total Bearing Height(mm)	Illustration
29749/29710		38.100	65.090	18.034	 Can <i>Bearings</i>
32010	5270344500 5270344530	50.000	80.000	20.000	 Can <i>Bearings</i>
52710-25000	52710-25000	0.000	0.000	0.000	
986714K1		70.000	107.000	21.500	
DAC38700037		38.000	70.000	37.000	 Can <i>Bearings</i>
DAC39740036/34		39.090	74.000	36.000	 Can <i>Bearings</i>
DAC4060 M1	51720-34100	40.000	80.000	36.000	 Can <i>Bearings</i>
DAC40800036/34		40.000	80.000	34.000	 Can <i>Bearings</i>
DAC42800036/34		42.000	80.000	36.000	 Can <i>Bearings</i>
GE25		25.000	42.000	20.000	 Can <i>Bearings</i>



V. Kan. Export

AN ISO/TS 16949:2009 CERTIFIED CO.

WORKS: PLOT NO.: 347, SECTOR-8, IMT-MANESAR, GURUGRAM-122050, HARYANA (INDIA)
TELEFAX: +91-124-406-7421, +91-9810049380, +91-9810099961
E.MAIL : canbearing@gmail.com , vaibhav.ahuja82@gmail.com

www.canbearings.com