




Can


SUITABLE FOR PETERBILT APPLICATION



ANTI FRICTION MOVEMENT
ROUND THE GLOBE



Can Bearing No.	O.E.M	Bore Dia(mm)	Outer Dia(mm)	Total Bearing Height(mm)	Illustration
212044/212011		60.330	122.240	38.100	 Can <i>Bearings</i>
212047/212011		63.500	122.238	38.100	 Can <i>Bearings</i>
212049/212011		66.675	122.238	38.100	 Can <i>Bearings</i>
218348/218210		89.974	146.975	40.000	 Can <i>Bearings</i>
3585/3525		41.280	87.312	30.162	 Can <i>Bearings</i>
3782/3720		44.450	93.264	30.162	 Can <i>Bearings</i>
580/572		82.550	139.992	36.512	 Can <i>Bearings</i>
594/592		95.250	152.400	39.688	 Can <i>Bearings</i>
598/592A		92.075	152.400	39.688	 Can <i>Bearings</i>



V. Kan. Export

AN ISO/TS 16949:2009 CERTIFIED CO.

WORKS: PLOT NO.: 347, SECTOR-8, IMT-MANESAR, GURUGRAM-122050, HARYANA (INDIA)
TELEFAX: +91-124-406-7421, +91-9810049380, +91-9810099961
E.MAIL : canbearing@gmail.com , vaibhav.ahuja82@gmail.com

www.canbearings.com