



Can

SUITABLE FOR VAUXHALL APPLICATION



ANTI FRICTION MOVEMENT
ROUND THE GLOBE



Can Bearing No.	O.E.M	Bore Dia(mm)	Outer Dia(mm)	Total Bearing Height(mm)	Illustration
11949/11910	11055109 330012 7413409	19.050	45.237	15.494	
45449/45410	03 28 022	29.000	50.292	14.224	
DAC 40780040	16 03 022	40.000	78.000	40.000	
DAC34660037		34.000	66.000	37.000	
DAC34670037		34.000	67.000	37.000	
DAC39720037		39.000	72.000	37.000	
DAC39720637		39.000	72.060	37.000	
DAC39740039		39.000	74.000	39.000	
VKC 2238		38.000	46.000	16.750	
VKC2215		0.000	0.000	0.000	



V. Kan. Export

AN ISO/TS 16949:2009 CERTIFIED CO.

WORKS: PLOT NO.: 347, SECTOR-8, IMT-MANESAR, GURUGRAM-122050, HARYANA (INDIA)
TELEFAX: +91-124-406-7421, +91-9810049380, +91-9810099961
E.MAIL : canbearing@gmail.com , vaibhav.ahuja82@gmail.com

www.canbearings.com